

# SEDNIATS-6400HD



**Features:**

- 64CH: 32\*6MP/1080P/960P/720P/D1@25/30fps,Preview:1/4/8/16/32/64(Chipset: Hi3536)
- H.265/H.264 Compression,Support 4K Output
- Dual-Streams Network transmission,Support 3G & WIFI extension
- Support IE,Chrome,Firefox,Safari Browser
- Smart video detection:motion detection,video blind,video loss
- P2P Service App name: VssMobile
- Support cloud storage :Dropbox,Google Drive
- Bandwidth:64CH 256Mbps(Up to 64CH 1080P@4M)
- Max upto 8 SATA Interfaces+1 eSATA Interface
- 3G mobile view (iPhone, Android, Blackberry, Symbian MS mobile)
- Power supply: 110V~220V±10%, 47Hz~63Hz

**Specifications:**

<b>Item</b>	H.265 Standalone 64CH NVR
<b>Model</b>	SAV-8164-CU
<b>System</b>	
Main Processor	1xHi3536
Operating System	Embedded Linux
Decode	16CH 1080P@30FPS
System Resources	Pentaplex function:live,recording,playback,backup&remote access
<b>Interface</b>	
User Interface	GUI,on-screen menu tips
Preview	1/4/8/16/32/64
<b>Video</b>	
Video Standards	PAL:625Line 50f/s;NTSC:525Line 60f/s
Video Compression	H.265/H.264 High Profile
Display Quality	TV:D1,VGA&HDMI:high definition(Max3840&times;2160) Support:3840&times;2160,1920&times;1080,1280&times;720,1024&times;768
Playback Quality	1080P/720P/960H/D1/HD1/CIF/QCIF
Video Input	Main stream:Up to 1920x2048 Auxiliary stream:D1
Motion Detect	Zones:192(16x12)detection zones,sensitivity:1-6
<b>Audio</b>	
Audio Compression	G.711A
Bidirectional Talk	Support

<b>Record and Playback</b>	
Record Mode	Manual>Alarm>Video Detection>Continuous
Local Playback	32ch 1080P /720P/D1
Search Mode	Time/Date,Alarm,Motion detection&exact search
<b>Storage and Backup</b>	
Space Occupation	1080P 80G/day/ch;720P 26G/day/ch;D1 16-20G/day/ch
Record Storage	HDD&Network
Backup Mode	Network download,USB,USB
<b>Interface</b>	
Elligent Analysis	N/A
Video Output	1ch BNC,1ch VGA,1ch HDMI
Audio Input	1ch
Audio Output	1channe IRCA(200-3000mV,5K&Omega;)
Alarm input	16CH
Alarm Output	4CH
Net Inteface	2 RJ45 10M/100M/1000M self-adaptive Ethernet interfaces
PTZ Protocol	1 RS-232 interface,1 RS-485 interface
USB	2xUSB
HDD	8 SATA Interfaces+1 eSATA Interface
3G/WIFI	Support
<b>Others</b>	
Onvif	Support ONVIF2.6
Power Consumption	<20W
Operation Temperature	0&deg;C-+55&deg;C
Operating humidity	10%-90%
Atmosphere	86kpa-106kpa
Power Supply	110V~220V&plusmn;10%, 47Hz~63Hz
Weight	7kg
Dimension	2U,441*448*88mm