

# SEDNIATS-2024V



## Specifications

<b>Item</b>	Dome IP Camera
<b>Model</b>	SEDNIATS 2024V
<b>Video</b>	
Audio	Microphone input and Line out/ two-way voice intercom
Bit Rate	128-8192kbps
Bit Rate Type	CBR/VBR
Compression	H.264 Main Profile/Baseline
Day and Night	Yes
Device Type	1440P AR0331 CMOS sensor
IR distance	30M
IR Filter	IR-CUT
IR-led	Yes,Day&Night
Min.Scene	Illumination 0.01lux(IR ON),WDR Function
Picture Resolution	2560*1440@ 30fps
S/N Ratio	>50DB
<b>Lens</b>	
lens	2.8-12mm lens
Viewing Angel	96-45°
<b>Function</b>	
Alarm input/output	1CH Input,1CH output(optional)
Alarm processing	Control center-PTZ preset pos-E-mail- Record-SD card
Alarm way	Motion Detection,Cover alarm
Aperture	Fixed Aperture F1.2
Audio Compression	G.711 / G.726
Audio input/ output	1CH Input,1CH output
Electronic shutter	1/5-1/15,000 /S
Ethernet	Ethernet (10/100 Base-T),RJ-45
Event action	E-mail / SMS / Zoom in alarm / Pop ap map / PTZ preset pos
Flip Config	Up/down, Left/right
Image enhancement	AWB/BLC / Brightness / Contrast/Saturation
Mobile Phone	iPhone,Android,Blackberry
Netork Protocal	HTTP / TCP/IP / SMTP / DHCP / UPNP / DDNS / DNS / ONVIF / 28181
Remote Access	DDNS / Software / P2P
Safety	IP address filtering,User level password protection,The user access
Software	IP Camera Client software
Software intelligence	Motion / Missed / Moving tracking / Counting / Retrograde detection
Software Management	CMS & ONVIFCompatible Devices
Steam flow	Support dual stream
Subtitles input	Channel name, Date/Time
WEB Browser	Microsoft Internet Explorer 6.0 and above,google,firefox etc.
<b>Physical properties</b>	
Accessories	Power adapter, Network cable, Stand, Operation manual, CD, Screw bag
Certification	CE ,FCC
Humidity	-10~85%
Power Comsumption	DC 12V ,Module power consumption is less than 2 W
Temperature	-20°~60°C