

IP Vandalproof Dome Camera, SEDNIATS-D213BH-50JL

- ◆ IP CAMERA,5.0Megapixel, 2592*1944
- ◆ Color waterproof camera, easy installation Type
- ◆ IR LEDs:31PCS; 30m IR night vision distance;
- ◆ Standard lens: 2.8-12mm Varifocal lens
- ◆ Color:White

Model NO.	SEDNIATS-D213BH-50JL
Network Camera	
Image Sensor	OS05A10
Main processor	HI3516D
Resolution	5.0Megapixel, 2592*1944
Effective Pixels	2592*1944
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec
Sync System	Internal
Usable Illumination	0.01Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Day/Night	Color/ B&W (IR-CUT)
Compression	H.264 / H.265
Image Config	Saturation/Brightness/Contrast/Sharpness, Mirror, 3D NR , White Balance, BLC
Motion Detection	Support
DWDR	DWDR
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian
Lens	
Focus Length	2.8-12mm Varifocal Lens
Focus Control	Manual
Lens Type	Manual
Pixels	3M Pixels
Auto Iris Support	NO
Night Vision	
Infrared LED	φ 5X30PCS
Infrared Distance	30M
IR Status	Under 1 Lux by CDS
IR Power On	CDS Auto Control
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4, HTTP, TCP/IP, FTP, NTP, RTSP, UDP, SMTP, DNS, DDNS
ONVIF	Support ONVIF 2.0
P2P	YES, Support QR Code
POE	Optional, Support IEEE 802.3af
WIFI	N/A
Video Delay	0.3S (Within the Lan)
Main Stream	2592*1944
Sub Stream	
IE Brower	IE6-11
Smart Phone	iPhone, iPad, Android, Android Pad
General	
Housing	Weatherproof , IP67
Anti-cut Bracket	YES,
IR Cut Filter	YES
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%,450mA

